



CRYONOMIC® Air Compressor (CAC) for dry ice blasters









- Integrated with an after cooler
- Special re-heater for dry ice blasting
- ✓ Ultra fine filters for compressed air quality according to German standard ZTV-ING Teil 3, Abs. 4





FEATURES & BENEFITS

- Stable regulation with large speed range, reduces fuel consumption
- Discharged starting of the engine **soft start** with compressor off load
- **Bolted individual panels** with detachable insulating mats low-cost and quick replacement
- Robust plastic protection protects the lighting elements
- **Hot-galvanised trailer chassis** including individual adoption longlife and versatile
- Large fuel filter with water separator and manual filling pump



TECHNICAL DATA	CAC 7-5	CAC 10-6	CAC 12-10
Suited for	COB62	COB62+ or COB71	СОМВІ73
Article number	P25060	P25080	P25110
Operation pressure (bar)	7	10	12
Volume flow (m³/min)	5.5	6.8	10.7
Cooling system	Water	Water	Water
Installed engine power (kW)	42	54,6	105
Speed at full capacity(rpm)	2700	2400	2200
Fuel tank capacity (I)	60	140	170
Sound power level (db(A))-Acc. to 2000/14/EC	98	≤98	99
Sound pressure level (db(A))-Acc. to ISO 3744 (r:10)	69	68	70
Weight	740 kg	1580 kg	2080 kg
Length	2980-3420 mm	4025-4100 mm	4380-4535 mm
Height & width	1370 mm	1525 mm	1770 mm
	· · · · ·	27.70 (((()))	

(*) Contact us for more information to personalise your compressor with your own logo and application picture (optional).





CRYONOMIC®
Kleimoer 3 - B-9030 Gent - Belgium
Tel: +32 9 216 76 90
info@cryonomic.com
www.cryonomic.com
CRYONOMIC® is a registered trademark of ARTIMPEX N.V.