



CRYONOMIC® Air Compressor (CAC) for dry ice blasters







rough handling on site



- Integrated with an after cooler
- Special re-heater for dry ice blasting
- Ultra fine filters for compressed air quality according to German standard ZTV-ING Teil 3, Abs. 4





FEATURES & BENEFITS

- Stable regulation with large speed range, reduces fuel consumption
- Discharged starting of the engine **soft start** with compressor off load
- **Bolted individual panels** with detachable insulating mats low-cost and quick replacement
- Robust plastic protection protects the lighting elements
- **Hot-galvanised trailer chassis** including individual adoption longlife and versatile
- Large fuel filter with water separator and manual filling pump



TECHNICAL DATA	CAC 10-6	CAC 10-10
Article number	P25080	P25090
Volume flow (m³/min) (cfm)	8.4 (300), 6.8 (240), 6.1 (215), 5.5 (195)	9.7 (342), 8.4 (300), 7.5 (265)
Operation pressure (bar) (psi)	7 (100), 10 (145), 12 (175), 14 (200)	10 (145), 12 (175), 14 (200)
Cooling system	Water	Water
Installed engine power (kW)	54.6	85
Speed at full load (rpm)	2400	2200
Fuel tank capacity (I) (gal)	140 (37)	170 (45)
Sound power level (db(A))-Acc. to 2000/14/EC	≤ 98	< 99
Sound pressure level (db(A))-Acc. to ISO 3744 (r:10)	76	70
Weight	1580 kg	1865 kg
Lenght	4370-4615 mm	4480-4720 mm
Height	1525 mm	1590 mm

(*) Contact us for more information to personalise your compressor with your own logo and application pictures (optional).





CRYONOMIC®
Kleimoer 3 - B-9030 Gent - Belgium
Tel: +32 9 216 76 90 - Fax: +32 9 216 76 91
info@cryonomic.com
www.cryonomic.com
CRYONOMIC® is a registered trademark of ARTIMPEX N.V.